



Seiya High-Wall Mounted Inverter Heat Pump

CODE		15	20	25	33	
Performance						
Indoor Unit	RAS-	B05J2KVG-E	B07J2KVG-E	B10J2KVG-E	B13J2KVG-E	
Outdoor Unit	RAS-	05J2AVG-E	07J2AVG-E	10J2AVG-E	13J2AVG-E	
Nominal	Cooling Capacity	kW	1.5	2.0	2.5	3.3
	Heating Capacity	kW	2.0	2.5	3.2	3.6
	EER/COP	W/W	4.05/4.26	3.77/3.91	3.25/3.72	3.00/3.91
UK	Cooling Total/Sensible	kW	1.47/1.22	1.95/1.57	2.44/1.93	3.22/2.49
	Heating	kW	1.18	1.60	2.03	2.20
Cooling EN14825	Range Min. - Max.	kW	0.75 - 2.00	0.76 - 2.60	0.80 - 3.00	1.00 - 3.60
	Power Input	kW	0.37	0.53	0.77	1.10
	Pdesign	kW	1.5	2	2.5	3.3
	SEER/Energy Efficiency Class		6.10/A++	6.10/A++	6.10/A++	6.10/A++
	Seasonal Energy Consumption	kWh/a	86	115	143	189
Heating EN14825	Range Min. - Max.	kW	0.90 - 3.00	0.92 - 3.30	1.00 - 3.90	1.10 - 4.50
	Power Input	kW	0.47	0.64	0.86	0.92
	Pdesign	kW	1.6	2.0	2.4	2.8
	SCOP/Energy Efficiency Class		4.00/A+	4.00/A+	4.00/A+	4.00/A+
	Seasonal Energy Consumption	kWh/a	560	699	839	980
Indoor Data		RAS-	B05J2KVG-E	B07J2KVG-E	B10J2KVG-E	B13J2KVG-E
Air Flow	High - Low	l/s	145 - 65	148 - 65	153 - 67	172 - 73
	High - Low	m ³ /h	522 - 234	534 - 234	552 - 240	618 - 264
Sound	Pressure High - Low	dB(A)	37 - 19	38 - 20	39 - 21	42 - 21
	Power High - Low	dB(A)	52 - 34	53 - 35	54 - 36	56 - 36
Unit	Height x Width x Depth	mm	293 x 798 x 230	293 x 798 x 230	293 x 798 x 230	293 x 798 x 230
	Weight	kg	9	9	9	9
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	16/14	16/14	16/14	16/14
Remote controller		WH-UC01NE (Infra-Red)	WH-UC01NE (Infra-Red)	WH-UC01NE (Infra-Red)	WH-UC01NE (Infra-Red)	
Outdoor Data		RAS-	05J2AVG-E	07J2AVG-E	10J2AVG-E	13J2AVG-E
Operating range	Cooling/Heating	°C	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24
Air Flow	High	m ³ /h - l/s	1800 - 500	1800 - 500	1800 - 500	1980 - 550
Sound	Pressure High Cooling/Heating	dB(A)	46/48	46/48	48/50	48/50
	Power High Cooling/Heating	dB(A)	61/63	61/63	63/65	63/65
Unit	Height x Width x Depth	mm	530 x 660 x 240	530 x 660 x 240	530 x 660 x 240	530 x 660 x 240
	Weight	kg	22	22	23	24
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4
	Min.-Max. Length	m	2-15	2-15	2-15	2-15
	Maximum Height Difference	m	±12	±12	±12	±12
	Drain Port Connection	mm	16	16	16	16
Refrigerant R32	Base Charge/Chargeless Length	kg/m	0.4/15	0.4/15	0.43/15	0.46/15
	Additional Charge	g/m	0	0	0	0
Run Current	Maximum	A	2.40	3.25	4.20	5.50
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-10	220-240/1/50-10	220-240/1/50-10	220-240/1/50-10

Accessories

RB-RXS30-E	Remote Controller	Weekly-timer, single combination
RB-RXS33-E	Remote Controller	Remote controller weekly-timer
RB-N103S-G	WiFi Control (model 24)	WiFi adapter
RB-N104S-G	WiFi Control (model 05-18)	WiFi adapter and cable





Seiya High-Wall Mounted Inverter Heat Pump (continued)

Performance

CODE			42	50	65
Indoor Unit		RAS-	B16J2KVG-E	18J2KVG-E	24J2KVG-E
Outdoor Unit		RAS-	16J2AVG-E	18J2AVG-E	24J2AVG-E
Nominal	Cooling Capacity	kW	4.2	5.0	6.5
	Heating Capacity	kW	5.0	5.4	7.0
	EER/COP	W/W	3.00/3.57	3.23/3.38	2.89/3.33
UK	Cooling Total/Sensible	kW	4.49/3.36	4.88/3.57	6.35/4.40
	Heating	kW	3.33	3.34	4.31
Cooling EN14825	Range Min. - Max.	kW	1.20 - 4.7	1.3 - 5.5	1.6 - 7.2
	Power Input	kW	1.40	1.55	2.25
	Pdesign	kW	4.2	5.0	6.5
	SEER/Energy Efficiency Class		6.10/A++	6.30/A++	6.10/A++
	Seasonal Energy Consumption	kWh/a	241	278	373
Heating EN14825	Range Min. - Max.	kW	1.30 - 6.00	1.0 - 6.0	1.6 - 8.1
	Power Input	kW	1.40	1.60	2.10
	Pdesign	kW	3.6	3.8	5.4
	SCOP/Energy Efficiency Class		4.00/A+	4.00/A+	4.00/A+
	Seasonal Energy Consumption	kWh/a	1259	1329	1890
Indoor Data		RAS-	B16J2KVG-E	18J2KVG-E	24J2KVG-E
Air Flow	High - Low	l/s	213 - 92	233 - 133	298 - 185
	High - Low	m ³ /h	768 - 330	840 - 480	1074 - 666
Sound	Pressure High - Low	dB(A)	43 - 22	48 - 32	48 - 35
	Power High - Low	dB(A)	58 - 37	63 - 47	63 - 50
Unit	Height x Width x Depth	mm	293 x 798 x 230	293 x 798 x 230	320 x 1050 x 250
	Weight	kg	10	9	14
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	16/14	16/14	16/14
Remote controller			WH-UC01NE (Infra-Red)	WH-UC01NE (Infra-Red)	WH-UC01NE (Infra-Red)
Outdoor Data		RAS-	16J2AVG-E	18J2AVG-E	24J2AVG-E
Operating range	Cooling/Heating	°C	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24
Air Flow	High	m ³ /h - l/s	2160 - 600	2160 - 600	2220 - 617
Sound	Pressure High Cooling/Heating	dB(A)	49/51	50/52	55/55
	Power High Cooling/Heating	dB(A)	64/66	65/67	70/70
Unit	Height x Width x Depth	mm	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290
	Weight	kg	30	34	38
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Min.-Max. Length	m	2-20	2-20	2-20
	Maximum Height Difference	m	±12	±12	±12
	Drain Port Connection	mm	16	16	16
Refrigerant R32	Base Charge/Chargeless Length	kg/m	0.62/15	0.88/15	1.08/15
	Additional Charge	g/m	20	20	20
Run Current	Maximum	A	7.19	7.50	10.55
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth
Power Supply*	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16	220-240/1/50-16	220-240/1/50-16

Accessories

RB-RXS30-E	Remote Controller	Weekly-timer, single combination
RB-RXS33-E	Remote Controller	Remote controller weekly-timer
RB-N103S-G	WiFi Control (model 24)	WiFi adapter
RB-N104S-G	WiFi Control (model 05-18)	WiFi adapter and cable



DIGITAL INVERTER



High-Wall Indoor Unit

RAV DI

CODE			25	36	50	67
Indoor Unit		RAV-	RM301KRTP-E	RM401KRTP-E	RM561KRTP-E	RM801KRTP-E
Outdoor Unit		RAV-	GM301ATP-E	GM401ATP-E	GM561ATP-E	GM801ATP-E
Nominal	Cooling Capacity	kW	2.5	3.6	5.0	6.7
	Heating Capacity	kW	3.4	4.0	5.3	7.7
	EER/COP	W/W	4.10/4.00	3.19/3.57	3.01/3.42	2.75/2.95
UK	Cooling Total/Sensible	kW	2.37/1.97	3.42/2.67	4.75/3.61	6.36/4.66
	Heating	kW	2.43	2.86	3.79	5.51
Cooling EN14825	Range Min. - Max.	kW	0.9 - 3.0	0.9 - 4.0	1.5 - 5.6	1.5 - 8.0
	Power Input	kW	0.61	1.13	1.66	2.44
	Pdesign	kW	2.5	3.6	5.0	6.7
	SEER/Energy Efficiency Class		6.36/A++	6.12/A++	6.19/A++	5.73/A+
	Seasonal Energy Consumption	kWh/a	138	206	283	409
Heating EN14825	Range Min. - Max.	kW	0.8 - 4.5	0.8 - 5.0	1.5 - 6.3	1.5 - 9.0
	Power Input	kW	0.85	1.12	1.55	2.61
	Pdesign	kW	2.6	2.7	2.8	5.1
	SCOP/Energy Efficiency Class		4.10/A+	4.22/A+	4.00/A+	4.01/A+
	Seasonal Energy Consumption	kWh/a	887	895	980	1780
Indoor Data		RAV-	RM301KRTP-E	RM401KRTP-E	RM561KRTP-E	RM801KRTP-E
Air Flow	High - Medium - Low	l/s	186 - 150 - 125	194 - 161 - 125	267 - 231 - 189	289 - 253 - 189
	High - Medium - Low	m ³ /h	670 - 540 - 450	700 - 580 - 450	960 - 830 - 680	1040 - 910 - 680
Sound	Pressure High - Medium - Low	dB(A)	40 - 34 - 29	41 - 36 - 30	42 - 39 - 36	45 - 41 - 35
	Power High - Medium - Low	dB(A)	55 - 49 - 44	55 - 51 - 45	57 - 54 - 51	60 - 56 - 51
Unit	Height x Width x Depth	mm	293 x 798 x 230	293 x 798 x 230	320 x 1050 x 250	320 x 1050 x 250
	Weight	kg	10	10	14	14
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	VP16/14	VP16/14	VP16/14	VP16/14
Remote Controller			WH-TA09NE	WH-TA09NE	WH-TA09NE	WH-TA09NE
Outdoor Data		RAV-	GM301ATP-E	GM401ATP-E	GM561ATP-E	GM801ATP-E
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15
Air Flow	High	m ³ /h - l/s	1800 - 500	2200 - 611	2400 - 667	2700 - 750
Sound	Pressure High Cooling/Heating	dB(A)	46/47	49/50	46/48	48/52
	Power High Cooling/Heating	dB(A)	61/62	64/65	63/65	65/69
Unit	Height x Width x Depth	mm	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290
	Weight	kg	29	34	40	42
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	5/8 - 3/8
	Min.-Max. Length	m	2-20	2-20	5-30	5-30
	Maximum Height Difference	m	±10	±10	±10	±10
	Drain Port Connection	mm	16	16	16	16
Refrigerant	Gas - Base Charge/Chargeless Length	m	R32 - 0.63/15	R32 - 0.9/15	R32 - 0.9/20	R32 - 1.3/20
	Additional Charge Liquid Side	g/m	20	20	20	35
Run Current	Maximum	Amps	4.17	5.60	7.78	12.23
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-10	220-240/1/50-10	220-240/1/50-16	220-240/1/50-16

Accessories

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-MTSC2	Mini Touch Screen Controller	Mini touch screen controller with configurable icons with schedule timer
RBC-AMS55E-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
RBC-SMF1	Fan Interface	Interface to provide an output to enable an external fan from the unit
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space



DIGITAL INVERTER



High-Wall Indoor Unit (continued)

CODE			90	100	100
Indoor Unit		RAV-	GM901KRTP-E	GM1101KRTP-E	GM1101KRTP-E
Outdoor Unit		RAV-	GM901ATP-E	GM1101ATP-E	GM1101AT8P-E
Nominal	Cooling Capacity	kW	8.0	9.5	9.5
	Heating Capacity	kW	9.0	11.2	11.2
	EER/COP	W/W	3.00/3.10	3.20/3.23	3.20/3.23
UK	Cooling Total/Sensible	kW	7.83/6.35	9.28/7.22	9.28/7.22
	Heating	kW	6.12	6.93	6.93
Cooling EN14825	Range Min. - Max.	kW	1.9 - 8.8	3.0 - 11.2	3.0 - 11.2
	Power Input	kW	2.67	2.97	2.97
	Pdesign	kW	6.7	9.50	9.50
	SEER/Energy Efficiency Class		6.10/A++	6.10/A++	6.10/A++
	Seasonal Energy Consumption	kWh/a	459	545	545
Heating EN14825	Range Min. - Max.	kW	1.6 - 9.9	3.0 - 13.0	3.0 - 13.0
	Power Input	kW	2.90	3.47	3.47
	Pdesign	kW	5.1	8.00	8.00
	SCOP/Energy Efficiency Class		4.10/A+	4.20/A+	4.20/A+
	Seasonal Energy Consumption	kWh/a	2151	2665	2664
Indoor Data		RAV-	GM901KRTP-E	GM1101KRTP-E	GM1101KRTP-E
Air Flow	High - Medium - Low	l/s	328 - 253 - 189	447 - 375 - 328	447 - 375 - 328
	High - Medium - Low	m ³ /h	1180 - 910 - 680	1610 - 1350 - 1180	1610 - 1350 - 1180
Sound	Pressure High - Medium - Low	dB(A)	47 - 41 - 35	49 - 45 - 41	49 - 45 - 41
	Power High - Medium - Low	dB(A)	62 - 56 - 50	64 - 60 - 56	64 - 60 - 56
Unit	Height x Width x Depth	mm	320 x 1050 x 250	348 x 1200 x 280	348 x 1200 x 280
	Weight	kg	14	19	19
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	VP16/14	VP16/14	VP16/14
Remote Controller			WH-TA09NE	WH-TA09NE	WH-TA09NE
Outdoor Data		RAV-	GM901ATP-E	GM1101ATP-E	GM1101AT8P-E
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15
Air Flow	High	m ³ /h - l/s	2900 - 806	4080 - 1133	4080 - 1133
Sound	Pressure High Cooling/Heating	dB(A)	51/68	54/57	54/57
	Power High Cooling/Heating	dB(A)	68/72	70/74	70/74
Unit	Height x Width x Depth	mm	630 x 800 x 300	890 x 900 x 320	890 x 900 x 320
	Weight	kg	47	68	68
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Min.-Max. Length	m	5-50	5-50	5-50
	Maximum Height Difference	m	±10	±10	±10
	Drain Port Connection	mm	16	16	16
Refrigerant	Gas - Base Charge/Chargeless Length	m	R32 - 2.0/20	R32 - 2.1/20	R32 - 2.1/20
	Additional Charge Liquid Side	g/m	35	35	35
Run Current	Maximum	Amps	14.02	16.80	5.60
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-20	220-240/1/50-20	380-415/3/50-10

Accessories

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-MTSC2	Mini Touch Screen Controller	Mini touch screen controller with configurable icons with schedule timer
RBC-AMS55E-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
RBC-SMF1	Fan Interface	Interface to provide an output to enable an external fan from the unit
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space