



Seiya (E2) High-Wall Mounted Inverter Heat Pump

CODE		15	20	25	33	
Performance						
Indoor Unit		RAS-	B05E2KVG-E	B07E2KVG-E	B10E2KVG-E	B13E2KVG-E
Outdoor Unit		RAS-	05E2AVG-E	07E2AVG-E	10E2AVG-E	13E2AVG-E
Nominal	Cooling Capacity	kW	1.5	2.0	2.5	3.3
	Heating Capacity	kW	2.0	2.5	3.2	3.6
	EER/COP	W/W	4.17/4.26	3.77/3.91	3.57/3.72	3.00/3.91
UK	Cooling Total/Sensible	kW	1.47/1.22	1.95/1.57	2.44/1.93	3.22/2.49
	Heating	kW	1.18	1.60	2.03	2.20
Cooling EN14825	Range Min. - Max.	kW	0.75 - 2.00	0.76 - 2.60	0.80 - 3.00	1.20 - 3.60
	Power Input	kW	0.36	0.53	0.70	1.10
	Pdesign	kW	1.5	2.0	2.5	3.3
	SEER/Energy Efficiency Class		6.90/A++	6.90/A++	7.00/A++	7.00/A++
	Seasonal Energy Consumption	kWh/a	=P13	101	125	165
Heating EN14825	Range Min. - Max.	kW	0.8 - 3.00	0.82 - 3.30	0.95 - 3.90	0.97 - 4.50
	Power Input	kW	0.47	0.64	0.86	0.92
	Pdesign	kW	1.6	2.0	2.4	2.7
	SCOP/Energy Efficiency Class		4.60/A++	4.60/A++	4.60/A++	4.60/A++
	Seasonal Energy Consumption	kWh/a	487	609	730	822
Indoor Data						
Air Flow		RAS-	B05E2KVG-E	B07E2KVG-E	B10E2KVG-E	B13E2KVG-E
Air Flow	High - Low	l/s	34 - 55	140 - 58	144 - 64	158 - 72
	High - Low	m³/h	48 - 199	500 - 209	510 - 233	560 - 259
Sound	Pressure High - Low	dB(A)	37 - 19	38 - 19	39 - 20	42 - 20
	Power High	dB(A)	50	51	52	54
Unit	Height x Width x Depth	mm	288 x 770 x 225	288 x 770 x 225	288 x 770 x 225	288 x 770 x 225
	Weight	kg	9	9	9	9
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	16/14	16/14	16/14	16/14
Remote controller			WH-TG01NE	WH-TG01NE	WH-TG01NE	WH-TG01NE
Outdoor Data						
Operating range		RAS-	05E2AVG-E	07E2AVG-E	10E2AVG-E	13E2AVG-E
Operating range	Cooling/Heating	°C	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24
Air Flow	High	m³/h - l/s	1690 - 470	1800 - 500	1800 - 500	1980 - 550
Sound	Pressure High Cooling/Heating/Silent	dB(A)	47/48/42	47/49/42	47/49/43	48/49/43
	Power High Cooling/Heating/Silent	dB(A)	60/61/55	60/62/55	60/62/56	61/62/56
Unit	Height x Width x Depth	mm	530 x 660 x 240	530 x 660 x 240	530 x 660 x 240	530 x 660 x 240
	Weight	kg	21	21	22	22
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4
	Min.-Max. Length	m	2-15	2-15	2-15	2-15
	Maximum Height Difference	m	±12	±12	±12	±12
	Drain Port Connection	mm	16	16	16	16
Refrigerant R32	Base Charge/Chargeless Length	kg/m	0.34/15	0.34/15	0.49/15	0.54/15
	Additional Charge	g/m	0	0	0	0
Run Current	Maximum	A	-/*	-/*	-/*	-/*
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-10	220-240/1/50-10	220-240/1/50-10	220-240/1/50-10
* Waiting for published data.						

Accessories

RB-RXS33-E	Remote Controller	Remote controller weekly-timer (WH-TA15PE)
RB-N105S-G	WiFi Control (model 24)	WiFi adapter
RB-N106S-G	WiFi Control (model 05-18)	WiFi adapter and cable



Wall installation



Self-cleaning



Automatic restart



Hi-power



Auto-diagnosis



Single-split



Remote control included



Dry function



ECO logic



Drain connection both sides



Seiya (E2) High-Wall Mounted Inverter Heat Pump (continued)

CODE			42	50	65
Performance					
Indoor Unit		RAS-	B16E2KVG-E	18E2KVG-E	24E2KVG-E
Outdoor Unit		RAS-	16E2AVG-E	18E2AVG-E	24E2AVG-E
Nominal	Cooling Capacity	kW	4.2	5.0	6.5
	Heating Capacity	kW	5.0	5.4	7.0
	EER/COP	W/W	3.31/3.73	3.33/3.60	2.89/3.33
UK	Cooling Total/Sensible	kW	4.49/3.36	4.88/3.57	6.35/4.40
	Heating	kW	3.33	3.34	4.31
Cooling EN14825	Range Min. - Max.	kW	1.40 - 4.70	1.45 - 5.50	1.7 - 7.2
	Power Input	kW	1.27	1.50	2.25
	Pdesign	kW	4.2	5.0	6.5
	SEER/Energy Efficiency Class		7.00/A++	7.00/A++	6.90/A++
	Seasonal Energy Consumption	kWh/a	210	250	330
Heating EN14825	Range Min. - Max.	kW	1.30 - 6.00	1.35 - 6.00	1.5 - 8.1
	Power Input	kW	1.34	1.50	2.10
	Pdesign	kW	3.6	3.8	5.4
	SCOP/Energy Efficiency Class		4.60/A++	4.40/A+	4.30/A+
	Seasonal Energy Consumption	kWh/a	1095	1209	1757
Indoor Data					
Air Flow		RAS-	B16E2KVG-E	18E2KVG-E	24E2KVG-E
Air Flow	High - Low	l/s	213 - 92	233 - 133	298 - 185
	High - Low	m³/h	760 - 330	840 - 480	1070 - 666
Sound	Pressure High - Low	dB(A)	43 - 22	48 - 26	48 - 29
	Power High	dB(A)	56	60	61
Unit	Height x Width x Depth	mm	293 x 798 x 230	293 x 798 x 230	320x1050x250
	Weight	kg	9	9	15
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	16/14	16/14	16/14
Remote controller			WH-TG01NE	WH-TG01NE	WH-TG01NE
Outdoor Data					
Operating range		RAS-	16E2AVG-E	18E2AVG-E	24E2AVG-E
Operating range	Cooling/Heating	°C	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24
Air Flow	High	m³/h - l/s	2160 - 600	2160 - 600	2220 - 617
Sound	Pressure High Cooling/Heating/Silent	dB(A)	50/51/43	50/51/44	54/54/49
	Power High Cooling/Heating/Silent	dB(A)	63/64/59	63/64/59	67/67/62
Unit	Height x Width x Depth	mm	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290
	Weight	kg	30	34	38
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Min.-Max. Length	m	2-20	2-20	2-20
	Maximum Height Difference	m	±12	±12	±12
	Drain Port Connection	mm	16	16	16
Refrigerant R32	Base Charge/Chargeless Length	kg/m	0.68/15	0.93/15	1.18/15
	Additional Charge	g/m	20	20	20
Run Current	Maximum	A	-/*	-/*	10.60
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16	220-240/1/50-16	220-240/1/50-16
* Waiting for published data.					

Accessories

RB-RXS33-E	Remote Controller	Remote controller weekly-timer (WH-TA15PE)	
RB-N105S-G	WiFi Control (model 24)	WiFi adapter	
RB-N106S-G	WiFi Control (model 05-18)	WiFi adapter and cable	



Wall installation



Self-cleaning



Automatic restart



Hi-power



Auto-diagnosis



Single-split



Remote control included



Dry function



ECO logic



Drain connection both sides

SHORAI Edge



Shorai Edge High-Wall Mounted Inverter Heat Pump

CODE		25	35	46	50	61	70	
Performance								
Indoor Unit		RAS-	B10J2KVSG-E	B13J2KVSG-E	B16J2KVSG-E	B18J2KVSG-E	B22J2KVSG-E	B24J2KVSG-E
Outdoor Unit		RAS-	10J2AVSG-E1	13J2AVSG-E1	16J2AVSG-E1	18J2AVSG-E	22J2AVSG-E	24J2AVSG-E
Nominal	Cooling Capacity	kW	2.5	3.5	4.6	5.0	6.1	7.0
	Heating Capacity	kW	3.2	4.2	5.5	6.0	7.0	8.0
	EER/COP	W/W	4.63/4.57	3.89/3.89	3.41/3.62	3.52/3.77	3.07/3.72	3.11/3.40
UK	Cooling Total/Sensible	kW	2.44/2.03	3.42/2.74	4.49/3.56	4.88/3.57	5.96/4.24	6.84/4.71
	Heating	kW	2.05	2.61	3.59	3.83	3.98	5.27
Cooling EN14825	Range Min. - Max.	kW	0.89 - 3.20	1.00 - 4.10	1.20 - 5.30	1.20 - 6.00	1.39 - 6.70	1.70 - 7.70
	Power Input	kW	0.54	0.90	1.35	1.42	1.99	2.25
	Pdesign	kW	2.5	3.5	4.6	5.0	6.1	7.0
	SEER/Energy Efficiency Class		8.60/A+++	8.60/A+++	7.80/A++	7.80/A++	7.30/A++	6.30/A++
	Seasonal Energy Consumption	kWh/a	102	142	206	224	292	389
Heating EN14825	Range Min. - Max.	kW	0.90 - 4.80	1.00 - 5.30	1.10 - 6.50	1.10 - 6.50	1.15 - 7.50	1.70 - 8.80
	Power Input	kW	0.70	1.08	1.52	1.59	1.88	2.35
	Pdesign	kW	2.5	3.2	4.0	4.3	4.7	6.3
	SCOP/Energy Efficiency Class		5.10/A+++	5.10/A+++	4.60/A++	4.60/A++	4.60/A++	4.10/A+
	Seasonal Energy Consumption	kWh/a	686	878	1217	1309	1430	2149

Indoor Data		RAS-	B10J2KVSG-E	B13J2KVSG-E	B16J2KVSG-E	B18J2KVSG-E	B22J2KVSG-E	B24J2KVSG-E
Air Flow	High - Low	l/s	183 - 86	203 - 95	213 - 100	274 - 158	299 - 191	316 - 199
	High - Low	m³/h	660 - 312	732 - 342	768 - 360	990 - 570	1,080 - 690	1140 - 720
Sound	Pressure High - Low	dB(A)	40 - 19	43 - 19	44 - 22	44 - 26	46 - 27	48 - 28
	Power High - Low	dB(A)	55 - 34	58 - 34	59 - 37	59 - 41	61 - 42	63 - 43
Unit	Height x Width x Depth	mm	293 x 800 x 226	293 x 800 x 226	293 x 800 x 226	320 x 1053 x 245	320 x 1053 x 245	320 x 1053 x 245
	Weight	kg	10	10	10	14	14	14
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	16/14	16/14	16/14	16/14	16/14	16/14
Remote Controller			WH-TA15PE	WH-TA15PE	WH-TA15PE	WH-TA12PE	WH-TA12PE	WH-TA12PE

Outdoor Data		RAS-	10J2AVSG-E1	13J2AVSG-E1	16J2AVSG-E1	18J2AVSG-E	22J2AVSG-E	24J2AVSG-E
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24	-15 to 46/-15 to 24
Air Flow	High	m³/h - l/s	1890 - 524	1950 - 540	2040 - 566	2076 - 576	2184 - 607	2916 - 810
Sound	Pressure High Cooling/Heating	dB(A)	44/46	46/48	48/50	48/50	49/51	50/52
	Power High Cooling/Heating	dB(A)	57/59	59/61	61/63	61/63	62/64	63/65
Unit	Height x Width x Depth	mm	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290	630 x 800 x 300
	Weight	kg	26	30	33	34	34	42
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Min.-Max. Length	m	2-20	2-20	2-20	2-20	2-20	2-25
	Maximum Height Difference	m	±12	±12	±12	±12	±12	±15
	Drain Port Connection	mm	16	16	16	16	16	16
Refrigerant R32	Base Charge/Chargeless Length	kg/m	0.55/15	0.8/15	0.8/15	1.1/15	1.1/15	1.14/15
	Additional Charge	g/m	20	20	20	20	20	20
Run Current	Maximum	A	3.75	5.35	7.55	8.35	9.11	11.16
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth	3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-10	220-240/1/50-10	220-240/1/50-16	220-240/1/50-16	220-240/1/50-16	220-240/1/50-16

Accessories

RB-RXS33-E	Remote Controller	Remote controller weekly-timer (WH-TA15PE)	
RB-N105S-G	WiFi Control (model 10-24)	WiFi adapter	



Wall installation



Self-cleaning



Automatic restart



Hi-power



Auto-diagnosis



Single-split



Remote control included



DRY Dry function



ECO ECO logic



Drain connection both sides



Anti-dust pre-filter



Toshiba IAQ filter



TOSHIBA



High-Wall Indoor Unit




CODE			25	36	50	67
Indoor Unit		RAV-	RM301KRTP-E	RM401KRTP-E	RM561KRTP-E	RM801KRTP-E
Outdoor Unit		RAV-	GM301ATP-E	GM401ATP-E	GM561ATP-E	GM801ATP-E
Nominal	Cooling Capacity	kW	2.5	3.6	5.0	6.7
	Heating Capacity	kW	3.4	4.0	5.3	7.7
	EER/COP	W/W	4.10/4.00	3.19/3.57	3.01/3.42	2.75/2.95
UK	Cooling Total/Sensible	kW	2.37/1.97	3.42/2.67	4.75/3.61	6.36/4.66
	Heating	kW	2.43	2.86	3.79	5.51
Cooling EN14825	Range Min. - Max.	kW	0.9 - 3.0	0.9 - 4.0	1.5 - 5.6	1.5 - 8.0
	Power Input	kW	0.61	1.13	1.66	2.44
	Pdesign	kW	2.5	3.6	5.0	6.7
	SEER/Energy Efficiency Class		6.36/A++	6.12/A++	6.19/A++	5.73/A+
	Seasonal Energy Consumption	kWh/a	138	206	283	409
Heating EN14825	Range Min. - Max.	kW	0.8 - 4.5	0.8 - 5.0	1.5 - 6.3	1.5 - 9.0
	Power Input	kW	0.85	1.12	1.55	2.61
	Pdesign	kW	2.6	2.7	2.8	5.1
	SCOP/Energy Efficiency Class		4.10/A+	4.22/A+	4.00/A+	4.01/A+
	Seasonal Energy Consumption	kWh/a	887	895	980	1780




Indoor Data		RAV-	RM301KRTP-E	RM401KRTP-E	RM561KRTP-E	RM801KRTP-E
Air Flow	High - Medium - Low	l/s	186 - 150 - 125	194 - 161 - 125	267 - 231 - 189	289 - 253 - 189
	High - Medium - Low	m³/h	670 - 540 - 450	700 - 580 - 450	960 - 830 - 680	1040 - 910 - 680
Sound	Pressure High - Medium - Low	dB(A)	40 - 34 - 29	41 - 36 - 30	42 - 39 - 36	45 - 41 - 35
	Power High - Medium - Low	dB(A)	55 - 49 - 44	55 - 51 - 45	57 - 54 - 51	60 - 56 - 51
Unit	Height x Width x Depth	mm	293 x 798 x 230	293 x 798 x 230	320 x 1050 x 250	320 x 1050 x 250
	Weight	kg	10	10	14	14
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	VP16/14	VP16/14	VP16/14	VP16/14
Remote Controller			WH-TA09NE	WH-TA09NE	WH-TA09NE	WH-TA09NE




Outdoor Data		RAV-	GM301ATP-E	GM401ATP-E	GM561ATP-E	GM801ATP-E
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15
Air Flow	High	m³/h - l/s	1800 - 500	2200 - 611	2400 - 667	2700 - 750
Sound	Pressure High Cooling/Heating	dB(A)	46/47	49/50	46/48	48/52
	Power High Cooling/Heating	dB(A)	61/62	64/65	63/65	65/69
Unit	Height x Width x Depth	mm	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290
	Weight	kg	29	34	40	42
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	5/8 - 3/8
	Min.-Max. Length	m	2-20	2-20	5-30	5-30
	Maximum Height Difference	m	±10	±10	±30	±30
	Drain Port Connection	mm	16	16	16	16
Refrigerant	Gas - Base Charge/Chargeless Length	m	R32 - 0.63/15	R32 - 0.9/15	R32 - 0.9/20	R32 - 1.3/20
	Additional Charge Liquid Side	g/m	20	20	20	35
Run Current	Maximum	Amps	4.17	5.60	7.78	12.23
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-10	220-240/1/50-10	220-240/1/50-16	220-240/1/50-16

Accessories

RBC-AMTU31-E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-MTSC2	Mini Touch Screen Controller	Mini touch screen controller with configurable icons with schedule timer
RBC-AMSU51-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
RBC-SMF1	Fan Interface	Interface to provide an output to enable an external fan from the unit
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space

-  Wall installation
-  Self-cleaning
-  Automatic restart

-  Auto-diagnosis
-  Single-split
-  Drain connection both sides

-  Chargeless
-  Low ambient cooling to -15°C DB
-  Remote control included

DIGITAL INVERTER



High-Wall Indoor Unit (continued)


CODE			90	100	100
Indoor Unit	RAV-		GM901KRTP-E	GM1101KRTP-E	GM1101KRTP-E
Outdoor Unit	RAV-		GM901ATP-E	GM1101ATP-E	GM1101AT8P-E
Nominal	Cooling Capacity	kW	8.0	9.5	9.5
	Heating Capacity	kW	9.0	11.2	11.2
	EER/COP	W/W	3.00/3.10	3.20/3.23	3.20/3.23
UK	Cooling Total/Sensible	kW	7.83/6.35	9.28/7.22	9.28/7.22
	Heating	kW	6.12	6.93	6.93
Cooling EN14825	Range Min. - Max.	kW	1.9 - 8.8	3.0 - 11.2	3.0 - 11.2
	Power Input	kW	2.67	2.97	2.97
	Pdesign	kW	6.7	9.50	9.50
	SEER/Energy Efficiency Class		6.10/A++	6.10/A++	6.10/A++
	Seasonal Energy Consumption	kWh/a	459	545	545
Heating EN14825	Range Min. - Max.	kW	1.6 - 9.9	3.0 - 13.0	3.0 - 13.0
	Power Input	kW	2.90	3.47	3.47
	Pdesign	kW	5.1	8.00	8.00
	SCOP/Energy Efficiency Class		4.10/A+	4.20/A+	4.20/A+
	Seasonal Energy Consumption	kWh/a	2151	2665	2664

Indoor Data		RAV-	GM901KRTP-E	GM1101KRTP-E	GM1101KRTP-E
Air Flow	High - Medium - Low	l/s	328 - 253 - 189	447 - 375 - 328	447 - 375 - 328
	High - Medium - Low	m³/h	1180 - 910 - 680	1610 - 1350 - 1180	1610 - 1350 - 1180
Sound	Pressure High - Medium - Low	dB(A)	47 - 41 - 35	49 - 45 - 41	49 - 45 - 41
	Power High - Medium - Low	dB(A)	62 - 56 - 50	64 - 60 - 56	64 - 60 - 56
Unit	Height x Width x Depth	mm	320 x 1050 x 250	348 x 1200 x 280	348 x 1200 x 280
	Weight	kg	14	19	19
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	VP16/14	VP16/14	VP16/14
Remote Controller			WH-TA09NE	WH-TA09NE	WH-TA09NE

Outdoor Data		RAV-	GM901ATP-E	GM1101ATP-E	GM1101AT8P-E
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15
Air Flow	High	m³/h - l/s	2900 - 806	4080 - 1133	4080 - 1133
Sound	Pressure High Cooling/Heating	dB(A)	51/68	54/57	54/57
	Power High Cooling/Heating	dB(A)	68/72	70/74	70/74
Unit	Height x Width x Depth	mm	630 x 800 x 300	890 x 900 x 320	890 x 900 x 320
	Weight	kg	47	68	68
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Min.-Max. Length	m	5-50	5-50	5-50
	Maximum Height Difference	m	±30	±30	±30
	Drain Port Connection	mm	16	16	16
Refrigerant	Gas - Base Charge/Chargeless Length	m	R32 - 2.0/20	R32 - 2.1/20	R32 - 2.1/20
	Additional Charge Liquid Side	g/m	35	35	35
Run Current	Maximum	Amps	14.02	16.80	5.60
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-20	220-240/1/50-20	380-415/3/50-10

Accessories

RBC-AMTU31-E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-MTSC2	Mini Touch Screen Controller	Mini touch screen controller with configurable icons with schedule timer
RBC-AMSU51-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
RBC-SMF1	Fan Interface	Interface to provide an output to enable an external fan from the unit
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space



Wall installation



Auto-diagnosis



Chargeless



Self-cleaning



Single-split



Low ambient cooling to -15°C DB



Automatic restart



Drain connection both sides



Remote control included